



125.018-6

Male elbow, swivel type, parallel male thread with O-ring (NBR)

Art. No.	Type No.	Ø D mm	Thread	Max. working pressure bar	A mm	B mm	C mm	E mm	H mm
109259	125.005-4	4	M5	15	4.0	18.6	14.9	18.8	8
109260	125.005-6	6	M5	15	4.0	19.6	16.0	20.1	8
109261	125.018-4	4	G 1/8	15	5.5	17.5	14.9	18.8	10
109262	125.018-6	6	G 1/8	15	5.5	18.5	16.0	20.0	10
109263	125.018-8	8	G 1/8	15	5.5	22.0	18.3	22.5	14
109264	125.018-10	10	G 1/8	15	5.5	23.3	21.0	26.9	17
109265	125.014-4	4	G 1/4	15	6.5	19.0	14.9	18.8	10
109266	125.014-6	6	G 1/4	15	6.5	20.0	16.0	20.0	10
109267	125.014-8	8	G 1/4	15	6.5	20.5	18.3	22.5	12
109268	125.014-10	10	G 1/4	15	6.5	24.3	21.0	26.9	17
109269	125.014-12	12	G 1/4	15	6.5	25.8	22.6	28.5	17
109270	125.038-6	6	G 3/8	15	7.5	21.1	16.0	20.0	12
109271	125.038-8	8	G 3/8	15	7.5	21.6	18.3	22.5	12
109272	125.038-10	10	G 3/8	15	7.5	22.8	21.0	26.9	20
109273	125.038-12	12	G 3/8	15	7.5	24.3	22.6	28.5	20
135638	125.038-14	14	G 3/8	15	7.5	31.7	24.3	33.3	20
109274	125.038-16	16	G 3/8	15	7.5	32.3	25.0	33.5	20
109275	125.012-6	6	G 1/2	15	9.0	23.5	16.0	20.0	12
109276	125.012-8	8	G 1/2	15	9.0	24.0	18.3	22.5	14
109277	125.012-10	10	G 1/2	15	9.0	25.7	21.0	26.9	17
109278	125.012-12	12	G 1/2	15	9.0	27.2	22.6	28.5	17
135639	125.012-14	14	G 1/2	15	9.0	29.9	24.3	33.3	24
109279	125.012-16	16	G 1/2	15	9.0	29.9	25.0	33.5	24